INK-JET PRINTER

EPSON[®] Stylus.800

Announcing a New Generation of Ink-Jet Desktop Printers



Advanced Epson technology finally gives you the fine resolution and clean images of a laser printer quickly, easily, and efficiently—all for less than you might expect. Compact and easy to operate, it's the ideal desktop printer for home and office applications.



SPECIFICATIONS

PRINTER TYPE			
PRINTING METHOD		ulti-layer Actuator Hea	ad)
NOZZLE CONFIGURATION			
PRINT DIRECTION	Bi-direction	nal printing with logic	seeking
PRINT SPEED			
LQ 10cpi	150cps		
LQ 12cpi	180cps		
LQ 15cpi	225cps		
LQ 17cpi LQ 20cpi	257cps 300cps		
PRINT CHARACTERISTIC	-		
CHARACTER SETS	6 characte	14 international chara r code tables 2437, PC850, PC860,	
BIT-MAP LQ FONTS	EPSON Ro EPSON Sa EPSON Co EPSON Pr	oman 10cpi, 12c ins Serif 10cpi, 12c ourier 10cpi, 12c estige 10cpi, 12c	pi, 15cpi, Proportional pi, 15cpi, Proportional pi, 15cpi pi
SCALABLE FONTS	EPSON So EPSON Ro EPSON Sa EPSON Ro EPSON Sa	oman 8pt to 32p ans Serif 8pt to 32p oman T 8pt to 32p	pi ot (every 2pt, 13 sizes) ot (every 2pt, 13 sizes) ot (every 2pt, 13 sizes) ot (every 2pt, 13 sizes)
CONTROL CODE			
	EPSON ES	SC/P2	
PRINTABLE COLUMNS			
LQ 10cpi	80		
LQ 12cpi	96		
LQ 15cpi	120		
LQ 17cpi	137		
LQ 20cpi	160		
PAPER HANDLING			
PAPER PATH		in Paper Feeder	
PAPER FEEDING METHOD	Friction fee	ed	
LINE SPACING			able in 1/360 inch steps
CUT SHEET	A4	210mm×297mm	(8.3''×11.7'')
(Built-in Paper Feeder)	Thickness Quality	0.065mm—0.14mm Bond paper, PPC	(0.0026''—0.0055'')
CUT SHEET	Width	182mm—216mm	(7.2''-8.5'')
(Manual insertion)	Length Thickness Quality	257mm—297mm 0.065mm—0.11mm Bond paper, PPC	(10.1''—11.7'') (0.0026''—0.0043'')
ENVELOPE	No.6	166mm×92mm	(6''1/2×3''5/8)
(Manual insertion)	No.10	240mm×104mm	(9''1/2×4''1/8)
	Thickness	0.16mm—0.52mm	(0.0063''—0.020'')

	32Kbyte (mixed text/graphics mode Off) 8Kbyte (mixed text/graphics mode On)	
INTERFACE		
The second second	Centronics®-type 8-bit Parallel Interface	
INK CARTRIDGE		
COLOR	Black	
TYPE	Exclusive ink cartridge	
INK CAPACITY	0.7 million characters	
INK LIFE	2 years from production date	
RELIABILITY		
MTBF	4000 power on hours	
PRINT HEAD LIFE	1000 million dots/nozzle	
TOTAL PRINT VOLUME	75000 pages (A4, Letter)	
CONTROL PANEL		
SELECTYPE		
SWITCHES	PAUSE, ECONOMY/CONDENSED, FONT,	
INDICATORS	LOAD/EJECT, ALT PAUSE, DATA, PAPER OUT, INK OUT,	
INDIOATONO	ECONOMY/CONDENSED, FONT	
ENVIRONMENTAL COND		
TEMPERATURE	10-35°C	
HUMIDITY	20—80% RH	
ELECTRICAL SPECIFICA	TIONS	
RATED VOLTAGE	120V	
	220V—240V	
RATED FREQUENCY	50—60Hz	
POWER CONSUMPTION	13W (Self test in LQ mode, 10cpi)	
DIMENSIONS		
W×D×H (without paper)	435×264×154mm	
WEIGHT	4.8kg	
CONSUMABLE		
INK CARTRIDGE	S020025	
ESC/P the standard printer langu Specifications are subject to chai Epson is the registered trademar	nge without notice.	

Epson Sourr 2 is a trademark of Selko Epson Corporation. Epson Stylus is a trademark of Selko Epson Corporation. Centronics is the registered trademark of Centronics Data Computer Corporation.

EPSON AUSTRALIA PTY LTD

Sydney: Unit 1, 17 Rodborough Rd Frenchs Forest NSW 2086 Phone: (02) 452 0666 Fax: (02) 975 4416

Perth: Level 5, 256 Adelaide Terrace Perth WA 6000 Phone: (09) 221 2744 Fax: (09) 325 6164

Melbourne: Level 1, Building 3, Riverside Quay, 6 Burne St South Melbourne VIC 3205 Phone: (03) 685 6555 Fax: (03) 686 1016

Bond paper, Air mail

Quality

Auckland: Epson House, 241-245 Hobson St Auckland NZ Phone: (09) 366 6855 Fax: (09) 366 6865

Brisbane: Level 3, Waterfront Place, 1 Eagle St Brisbane QLD 4000 Phone: (07) 360 0219 Fax: (07) 360 0289

Wellington: M.V. Marshall House 142-146 Wakefield St Wellington NZ Phone: (04) 385 2494 Fax: (04) 385 6975

A.C.N. 002 625 783